



SPECIFICATION SHEET	
CSI DIVISION:	<ul style="list-style-type: none"> • 06 46 00 WOOD TRIM, SOFFITS, PANELING • 07 46 00 WOOD SIDING
MANUFACTURER:	<ul style="list-style-type: none"> • Montana Timber Products
PRODUCT:	<ul style="list-style-type: none"> • ranchwood™ - No equal
SPECIES:	<ul style="list-style-type: none"> • Douglas Fir • Western Red Cedar
APPLICATIONS:	<ul style="list-style-type: none"> • Exterior - Siding, soffit, trim, fascia, and fencing • Interior - Wall & ceiling cladding
COATING PRODUCT:	<ul style="list-style-type: none"> • SEAL-ONCE® - Ultra-low VOC, water-based stain and sealer (applied on 4 sides of board w/ 2 face coats)
COLORS:	<ul style="list-style-type: none"> • Tackroom Prairie Eastern Western Yellowstone Greenhorn Southern Northern
STANDARD TEXTURES:	<ul style="list-style-type: none"> • Smooth Wire Brushed Circle Sawn Hand Hewn Pioneer
STANDARD PROFILES:	<ul style="list-style-type: none"> • T&G Square Edge Lap Shiplap Square Edge Channel Rustic
OPTIONAL FIRE TREATMENTS:	<ul style="list-style-type: none"> • Fireline™ - WUI compliant pressure treated fire retardant • Topical Coating - Shop-applied Class A fire retardant
LIMITED WARRANTY: (see document for complete details)	<ul style="list-style-type: none"> • 10 years for water ingress (vertical surfaces) • 5 years for water ingress (horizontal surfaces)

STANDARD SPECIES:	Douglas Fir	Cedar
STANDARD GRADE:	#2 & Btr	Select Tight Knot (STK)
OPTIONAL GRADES:	Clear Vertical Grain (CVG) Clear Mixed Grain (CMG)	Clear Vertical Grain (CVG), A & Btr Clear Mixed Grain (CMG), C & Btr
MOISTURE CONTENT (MC):	Kiln Dried (KD) to less than 15%	
NOMINAL THICKNESS:	1" & 2"	
NET THICKNESS:	3/4" & 1-3/4"	3/4" & 1-1/2"
NOMINAL WIDTHS:	4", 6", 8", 10", 12"	
NET WIDTHS:	3 3/4", 5 3/4", 7 3/4", 9 3/4", 11 3/4"	3 1/2", 5 1/2", 7 1/4", 9 1/4", 11 1/4"
LENGTHS:	Random Lengths: 8' - 20'	Random Lengths: 8' - 16'
NET SIZING:	Custom net sizing available	